





# IP RATED TRUNKING


For satin finish prefix reference number with a 'K'  
For mirror finish prefix reference number with a 'M'


Trunking - Lengths	W x H	Ref.
	100x100	F44-03
	150x100	F64-03
	150x150	F66-03


Tees - Outside Cover	W x H	Ref.
	100x100	F44-91
	150x100	F64-91
	150x150	F66-91


Tees - Front Cover	W x H	Ref.
	100x100	F44-92
	150x100	F64-92
	150x150	F66-92

Bends 90° - Inside Cover	W x H	Ref.
	100x100	F44-93
	150x100	F64-93
	150x150	F66-93

Bends 90° - Outside Cover	W x H	Ref.
	100x100	F44-94
	150x100	F64-94
	150x150	F66-94

Bends 90° - Front Cover	W x H	Ref.
	100x100	F44-95
	150x100	F64-95
	150x150	F66-95

Elbows 45° - Inside Cover	W x H	Ref.
	100x100	F44-16
	150x100	F64-16
	150x150	F66-16

Elbows 45° - Outside Cover	W x H	Ref.
	100x100	F44-17
	150x100	F64-17
	150x150	F66-17


## IP55 RATED TRUNKING


Lasnek IP55 rated trunking specifically designed for demanding applications where containment is required within low level washdown areas. Quick, easy to install and clean, the Lasnek IP55 trunking has all the advantages of traditional trunking but with the additional safeguard of ingress protection. All 3 metre lengths come complete with the unique Lasnek coupling arrangement and joining kit.




### Standard Features:

- n Material: 1.5mm 304 - 1.4301 stainless steel
- n Finish: Satin or Mirror
- n Lengths: 3 Metre complete with coupler and joint cover
- n Rating: BSI rated to IP55
- n Fittings: All cover configurations available

Elbows 45° - Front Cover	W x H	Ref.
	100x100	F44-18
	150x100	F64-18
	150x150	F66-18

End Caps	W x H	Ref.
	100x100	F44-21
	150x100	F64-21
	150x150	F66-21

Straight Couplings	W x H	Ref.
	100x100	F44-22
	150x100	F64-22
	150x150	F66-22